



SIGMARK

GUIDELINE



BERGER 

**ROAD
MARKING
&
KERB
COATINGS**
FOR INFRASTRUCTURE

Solvent-based Kerb Paint



Guideline SB RM Paint is a single pack, alkyd based, kerb and median marking paint which ensures safety on roads with excellent wear and weather resistance properties. It is suitable for kerb painting of new and existing concrete surfaces and precast concrete medians. It is recommended for concrete and paved block surfaces on city roads and also over steel rails and separators over a suitable primer/coating.

Full Gloss • Tough Film • Better Washability

DIRECTIONS FOR USE

SURFACE PREPARATION

Fresh / New Surfaces : Substrate must be fully cured, dry, sound and clean. Strip all loose particles from the surface by wire brushing. Alternatively, high pressure water jetting is recommended to ensure that the surface is free from curing materials, contaminants & dirt. Concrete should be fully cured and may need to be mechanically abraded or water blasted to remove any curing compounds.

Previously Painted Surfaces : All voids, dents are to be repaired and sealed. Surface should be cleaned by wire brushing to make it free from loose mortar, dirt, oil and grease etc.

DIRECTIONS FOR APPLICATION

Apply 1 coat of BP Cement Primer (ST) for concrete surfaces or 1 coat of BP Red Oxide Primer for metal surfaces – after proper thinning. Allow Primer to dry/cure fully before application of Guideline SB Paint. Dilute Guideline SB Paint as per recommended dilution ratio. Apply the first coat and allow to dry for at least 18-24 hours. After the first coat dries, apply the second coat and allow to dry for 18-24 hours.

** Depends on surface conditions, relative humidity, WFT and ambient temperature etc.

COVERAGE*

Substrate	Recommended No. of Coats	Airless Spray / Brush Application / Coat - TCC
Concrete	2	10.9 - 15.2 Sq. M / Litre
Metal		

* Depends on factors such as surface preparation, surface condition, application skill, weather conditions, dilution etc. The coverage mentioned above is under ideal conditions and will vary depending on site conditions.

Surface Recommended Primers

Concrete	1 coat of BP Cement Primer (ST)
Metal	1 coat of BP Red Oxide Primer

Pack Sizes Metal Drum (20 Lt)

Shade Range offered White, Golden Yellow, Black, Red



Usage Areas : On Concrete, Plastered & Metal surfaces.



BERGER
GUIDELINE

Guideline SB Paint
conforms to IS 2932 specifications

FOR DETAILED INSTRUCTIONS & METHODOLOGY,
REFER TECHNICAL DATA SHEET

Quick Drying Solvent-based Kerb & Line Paint



Guideline SB QD RM Paint is a single component, solvent-based quick drying road marking paint. It is formulated with a special grade of TP Acrylic Emulsion with unique drying properties. It provides excellent wear and weather resistance thus ensuring road safety. Suitable for application on kerbs, concrete and bituminous road surfaces, it has the unique capability of drying within 15 minutes**.

Quick Drying • Semi Glossy • High Opacity
• High Scrub Resistance

DIRECTIONS FOR USE

SURFACE PREPARATION

Fresh / New Surfaces : Strip all loose particles from the surface by wire brushing. Alternatively, high pressure water jetting is recommended to ensure that the surface is free from curing materials, contaminants and dirt. Concrete should be fully cured and may need to be mechanically abraded or water blasted to remove any curing compounds.

Previously Painted Surfaces : All voids, dents should be repaired and sealed. The surface should be cleaned by wire brushing to make it free from loose mortar, dirt, oil and grease etc.

DIRECTIONS FOR APPLICATION

Dilute the paint as per recommended dilution ratio. Stir well, preferably with a gyroshaker, and apply 1 coat of Guideline SB QD RM Paint and allow it to dry for at least 45-60** minutes. After the first coat dries, apply the second coat and allow it to dry for 60-75 minutes**

** Depends on surface conditions, relative humidity, WFT and ambient temperature etc.



COVERAGE*

Substrate	Recommended No. of Coats	Airless Spray / Brush Application / Coat - TCC
Concrete / Bitumen	2	7 - 11.2 Sq. M / Litre

* Depends on factors such as surface preparation, surface condition, application skill, weather conditions, dilution etc. The coverage mentioned above is under ideal conditions and will vary depending on site conditions.

Recommended Undercoats / PRIMERS
 No priming required

Pack Sizes Metal Drum (20 Lt)

Shade Range offered White, Golden Yellow, Black, Signal Red



Usage Areas Concrete, Bitumen & Asphalt surfaces.



BERGER
GUIDELINE

Guideline SB QD RM Paint
 conforms to IS 164 - 1981 specifications

FOR DETAILED INSTRUCTIONS & METHODOLOGY
 REFER TECHNICAL DATA SHEET